International Trailer Supply
Spec Sheet: 4-Stall

Model	4-Stall		**Door Style**	Private
Box Dimension	16' x 12' x 7' x 8'		**Axel #**	1
Stalls	2 Male | 2 Female		**Waste Tank Capacity**	348 Gallons

Size Specs & Details

Box Length	16 ft
Overall Length with Bumper & Hitch	20 ft 9 in
Box Width	7 ft
Overall Width (Doors Open Stairs Down)	9 ft 5 in
Interior Stall Height	6 ft 6 in
Interior Stall Length	3 ft 2 in
Exterior Height with A/C	11 ft 4 in
Fresh Water Capacity	300 gallons
Waste Tank Capacity	348 gallons
Curb Weight	4,189 lbs
Axel Rating	7,600 lbs straight shafted
Tire Rating	3,100 lbs per tire

Electric Specs & Details

50 Amp external power receptacle with 50 Amp Cord

50 Amp to 30 Amp or 15 Amp

Convertor Amp Max

Wiring	50 Amp
Breaker Control Board	50 Amp
A/C	16 Amp
Pump	1.45 Amp
All Receptacle	1.5 Amp
Water Heater (Optional)	12 Amp
Total Amp Load	**30.95 Amp Load**
Over/Under Amp Load	**19.05 Amp Load**

Exterior 50Amp Electric Recep (Minimum Power Requirements)

Exterior Power Source		**15 Amp/110V**	**30 Amp/220V**	**50 Amp/240V**
30 Ft Power Cord	1.5 Amps	☑	☑	☑
Light and Receptacles (not rated for high Amperage Appliance)	1.45 Amps	☑	☑	☑
1 Air Conditioner Unit	8 Amp to 16 Amp	☑	☑	☑
1 Water Heater	12 Amp	☑	☑	☑
2nd Air Conditioner Unit	8 Amp to 16 Amp	**NO**	☑	☑

Product Image	#	Name	Description
Trailer Exterior			
	1	Exterior Wall & Ceiling Material	1 1/2" White Fiberglass Exterior Walls. 1 3/8" Tan Fiberglass Interior Walls.
	2	Tires	16" ST235/80R16. Tubeless Radial DOT Certified Tires.
	1	Trailer Axle	7,000, Straight Shafted, under-slung, Leaf Spring Axles With an Electromagnetic Brakes.
	1	3" Waste Tank Relief Valve	3" Valve With a Quick Connect Adaptor and Cap. Located on the Front of the Trailer. 3" Waste Tank W/ Easy Access Cleaning Port 3" Ball Valve for Waste Tank Cleaning Access. Mounted on the Front of the Trailer
	1	Tongue Jack	Tongue Jack With A Flat Base And A Maximum Lift Capacity Of 10,000 lbs.
	4	Stabilizer Jacks	3000lb Support Capacity, 2000lb lift Capacity Trailer jack
	1	Hitch Coupler	2-5/18" Adjustable Position Hitch Coupler With A 20,000 lb. Weight Capacity.

	2	Safety Chains	Transport Chain, Clipped On The Trailer With Hooks For The Towing Truck. 3/8 Grade 70 ZP Ultimate Break: 26,400lbs
	1	Anti Release Emergency Brake System	Located On The A-Frame
	4	Restroom Entrance Handles	Easy-Lock Deadbolt With Privacy Indicator. A Polished Steel Metal Base. Key Lock On The Bottom To Lock During Transport.
	4	Slide Out Stairs	Aluminum Alloy Quad Slide-Out Stairs With A 300 lb. Rating.
	4	Swing Out Grab Handles	Fold Away stair grab handle.
	1	Trailer Lighting	DOT Certified Lighting.
	1	License Plate Holder	Brake Light With License Plate Holder On The Rear End.
	4	Soft Close Hinge Doors	Adjustable Door Closer. Soft Close, No Slam, for Doors Weighing 90-140 lbs. Hydraulic Door Spring - Black

	1	Secure T Lock	T-Lock On The Utility Room Door To Ensure That It Can Stay Open In Place.
	1	Porch Lights	12V Waterproof And Located Above All Compartment Doors.
	1	Waste Tank	348 Gallon polypropylene Waste Tank.
	1	Waste Tank Level	Reading Acrylic Viewing Window Used To Ensure Waste Tank Reading Is Accurate Without Need For Power.
Exterior Connections			
	1	City Water Inlet Connection	(Standard Hose) Connection.
	1	Fresh Water Tank Inlet Connection	ABS
	1	Fresh Water Outlet Valve	Fresh Water Drain Pipe To Release Any Leftover Water From The Freshwater Tank.

	1	City Power Connection	220V Power City Power Connection With Twist Lock.
	1	Aviation Truck Connection	8 ft Long 7-Way Trailer Plug-Cord Wiring Harness And Extension.
Utility Closet			
	1	Wiring	All Wires Neatly Together Throughout the Trailer with c-clamps And splice caps. 50 amp wiring
	1	Water Pump	110V AC Fresh Transfer Diaphragm Water Pump On Demand 5.5GPM 75PSI High Pressure Water Booster Pump.
	1	Quarter Turn Valves	1/4 Turn Valves Through The Trailer.
	1	Waterline Pipes	1/2" PEX Material Piping Through Out The Trailer.
	1	Stainless Steel Pex Clamps	1/2" Pex Clamps Throughout The Trailer.
	1	Air Conditioning And Heating	Furrion Chill Cube 18k BTU Variable Speed RV Rooftop Air Conditioner.

	1	Electricity Control Board	Siemens 125 Amps Main Lug Breaker Control Board.
	1	PE Fresh Water Tank	Reinforced, Custom 300 Gallon Fresh Water Tank.
Restroom Interior			
	4	Wash Station	Drop-in sink with a waste basket underneath the countertop
	4	Toilets	Thetford Aqua-Magic Style II Porcelain RV Toilet, White, High Profile. 20"D x 15"W x 19.5"H
	2	Toilet Flange Seal	Rubber RV Standard Toilet Flange Seal To Ensure A Proper Connection. With A Downpipe Into The Waste Tank.
	2	Urinals	Mansfield .5 GPF Porcelain Wall-Mounted Urinal.
	4	Hand Towel Dispenser	Lavex black multifold wall mounted plastic paper towel dispenser. 540 towel capacity. 11"L, 4 1/2"W, 16 1/16"H.

	4	Toilet Paper Dispenser	Lavex, Single Jumbo Roll, Wall mounted Toilet tissue dispenser.
	4	Hand Soap Dispenser	Wall Mounted Top-Fill Soap Dispenser, 800 - 1,000 mL.
	4	Sink Basin	Single Bowl Sink - 15-3/4" Long x 12-3/8" Wide - White, Plastic.
	4	Sink Faucet	Single-Handle, Matte Black Ceramic Cartridge, Stainless Steel Faucets.
	4	Sink Plumbing	Sink Plumbing With A Check Valve.
	1	Linoleum Flooring	Linoleum woodgrain Flooring. LT Commercial Grade.
	1	Lighting	4" Round LED, Hard Wired and Grommeted. 12V, 500/360 Lumens Lights.
	4	Mirror	28" x 30" Beveled Mirror.
	6	Power Outlet	110V Power Outlet

Note: Specifications, layouts, and standard equipment are subject to change without notice based on material availability and engineering improvements. Images may show optional upgrades.